





MORE CHOICES FOR EVERY REQUIREMENT

www.hikvision.com



For vigilant home and business owners, Hikvision offers a complete, professional-grade "Easy IP" video surveillance system that connects you to your entire property and gives you reassurance that it is safeguarded. This HD solution is easy to install, easy to connect, easy to store, and easy to view — allowing you to experience the true benefits and value that IP surveillance has to offer.



Common Concerns of Home and Business Owners

- I have trouble with IP address forwarding.
- It's difficult to deploy Ethernet cables in my shop.
- I want to monitor my store on my cell phone.
- Does higher resolution mean more storage expenses?
- I need more choices for different locations.

HOW THE HIKVISION EASY IP SOLUTION ADDRESSES THESE CONCERNS



EASY TO INSTALL

Hikvision's Easy IP solution makes the installation easy and secure.



Installation is a labor-intensive effort that requires an Ethernet cable and a power plug for the camera.

With the PoE NVR, you only need an Ethernet cable to connect the IP camera and NVR.



Several fixed cameras have to be installed to cover the entire store.

The whole shop is covered by one fisheye camera, reducing time and labor costs.

Picture 2



Stores often have existing downlights or at least designated areas for these lights. Using a recessed-mount dome, these spaces can be utilized without any re-work or construction.



Once a camera is installed, adjusting the lens is difficult.



With a PT (pan-tilt) camera, you can control the direction of the lens with a mouse.

EASY TO CONNECT

Hikvision's Easy IP solution offers Wi-Fi cameras, Wi-Fi NVRs, and PoE NVRs for easy connection. The system features automatic IP address allocation, auto detection, auto connection, and easy access.



For analog users, configuring the IP address forwarding can be a headache and may prevent them from choosing an IP solution. Hikvision's PoE NVR solves that problem for you and also saves time for mass configuration.



For some locations, deploying an Ethernet network for IP cameras is a constraint. A complete solution that incorporates Wi-Fi cameras and NVRs addresses this problem.

EASY TO STORE

Hikvision's Easy IP cameras offer high compression efficiency and reduce the burden of transmission and storage on the IP surveillance system.



Bandwidth and storage costs are significant concerns when considering a high definition IP system — a standard H.264 camera with full HD1080P resolution and one month of recording can result in about 1.2 TB of space consumed.



Hikvision's H.264+ optimized codec technology helps to reduce storage consumption by up to 1/3 compared to traditional IP systems – a H.264+ IP camera with full HD1080P resolution and one month of recording consumes about 462 GB.

EASY TO VIEW

All Hikvision Easy IP cameras support the EZVIZ Cloud P2P service, which enables remote access simply by using a smartphone to scan the supplied product $\ensuremath{\mathsf{QR}}$ code.



EZVIZ is a cloud platform to power the surveillance for more efficient security and business. With EZVIZ P2P service, you can view the live video and recorded video files of your house, your stores and your enterprise anytime and anywhere. Intelligent Alarm is supported for precisely recognize the anomaly intrusion and emergency event.

EASY IP SOLUTION

APPLICATION REFERENCE



McDonald's, Malaysia

The McDonald's corporation has installed a Hikvision IP system in every one of its more than 300 branches. Working alongside the existing analogue system for the moment, the new network system is fully integrated with the POS terminals and allows McDonald's retail managers to search and playback the entire transaction history for the shop.



The Centaurus Mall, Pakistan

Hikvision applied a set of IP system including network cameras, NVR and iVMS-5200 Professional software to secure the shopping mall's skyscrapers with video surveillance covering important locations and alarm systems in case of emergency, so as to well protect the customers and provide a safe consumer environment.



The Ramez group has utilized Hikvision's IP system with various front-end network cameras and backend recorders to monitor the market chain's parking facilities, and every individual rack of goods within the store, and to eliminate camera blind spots on retail floor space.



Kotoka International Airport, Ghana

Hikvision has completed the installation of an IP CCTV surveillance network for Aviance Ghana Ltd at Kotoka International Airport. A total of thirteen cameras now maintain close scrutiny of the 650 hectare site and protect passengers, aircraft and cargo.



Road-tanker Transport Business Company, South Africa

Hikvision has successfully completed the implementation of a state-of-the-art IP CCTV system to protect GRW's bespoke vehicle manufacturing premises, surveilling the perimeter of this large facility and protecting the plant from unauthorized access.

EASY TO CHOOSE

Hikvision's Easy IP solution offers an affordable way, and more choices to meet all of your needs.







MINI SIZE



- Full HD1080p
- 120dB WDR
- Fixed lens
- On-board storage
- 3-axis adjustment
- Up to 10m IR
- IK8 protection
- IP66
- Audio output/Mic optional (-S)
- Alarm I/0 (-S)
- Built-in Wi-Fi (-W)
- H.264+ Codec
- DC12V & PoE



- Full HD1080p
- 120dB WDR
- Fixed lens
- Up to 30m IR
- IP66
- Metallic housing
 DC12V & PoE
- H.264+ Codec



OUTDOOR

OUTDOOR



DS-2CD2642FWD-I 4MP VF IR Bullet DS-2CD2622FWD-I 2MP VF IR Bullet

DS-2CD2542FWD-I

DS-2CD2522FWD-I

DS-2CD2042WD-I

DS-2CD2022WD-I

4MP Mini Bullet

2MP Mini Bullet

4MP Mini Dome

2MP Mini Dome

- Full HD1080p
- 120dB WDR
- 2.8~12mm VF lens
- On-board storage
- Up to 30m IR
- IP66
- Metallic housing
- Audio/Alarm IO (-S)
- DC12V & PoE
- H.264+ Codec
- Motorized Lens (-Z)

NEW

DS-2DE4220IW-D 2MP 20X IR PTZ DS-2DE4120I-D 1.3MP 20X PTZ

- 2MP/1.3MP real-time
- 20X Optical Zoom
- H.264 codec
- 3D intelligent positioning function
- Support EZVIZ cloud P2P
- Up to 100m IR distance
- Compact-sized design



DS-2CD2E2OF 2MP Mini Dome DS-2CD2E1OF 1.3MP Mini Dome

- Full HD1080p or HD720p video
- Recessed mount for easy installation
- Fixed lens
- On-board storage
- DC12V & PoE
- Color cover optional (black/silver/golden)
- Built-in Wi-Fi (-W)



DS-2CD2342WD-I 4MP EXIR Turret DS-2CD2322WD-I 2MP EXIR Turret

DS-2CD2742FWD-I 4MP VF IR Dome

DS-2CD2722FWD-I

- Full HD1080p
- 120dB WDR
- Fixed lens
- Up to 30m IR
- IP66
- Metallic housing
 DC12V & PoE
- H.264+ Codec
- 11.2041 00000

T

2MP VF IR Dome

- Full HD1080p • 120dB WDR
- 2.8~12mm VF lens
- On-board storage
- Up to 30m IR
- IP66
- IP66
- Metallic housing
- Audio/Alarm IO (-S)
- DC12V & PoE
- H.264+ Codec
- Motorized Lens (-Z)







- Full HD1080p
- 120dB WDR
- Fixed lens
- Up to 80m IR (-18)
- IP66
- Metallic housing
- DC12V & PoE
- H.264+ Codec





PoE NVR



- 160/200Mbps bit rate input max(up to 16/32-ch IP video)
- Third-party network cameras supported
- Up to 5 megapixels resolution recording
- HDMI and VGA output at up to 1920×1080P resolution
- Gigabit network interfaces
- 4 ŠATA, 2 USB 2.0, 1 USB 3.0 *-E4/16P series support 16 independent PoE network
 - interfaces



- 40/80/160Mbps bit rate input max(up to 4/8/16-ch IP video)
- Third-party network cameras supported
- Up to 5 megapixels resolution recording
- HDMI and VGA output at up to 1920×1080P resolution
- 1 SATA(DS-7604NI-E1,DS-7604NI-E1/4P)
- 2 SATA(DS-7608/16NI-E2,DS-7608/16NI-E2/8P)
- *-E1/4P series support 4 independent PoE network interfaces
- *-E2/8P series support 8 independent PoE network interfaces
- *-E2/16P series support 16 independent PoE network interfaces



Wi-Fi NVR



DS-7108NI-E1/V/W DS-7108NI-E1/V/W/500G DS-7108NI-E1/V/W/1T Embedded Mini WiFi Router NVR

- 80Mbps bit rate input max(up to 8-ch IP video)
- Third-party network cameras supported
- Up to 6 megapixels resolution recording
- HDMI and VGA output at up to 1920×1080P resolution
- 1 SATA, 1 USB3.0
- 802.11 b/g/n and a built-in dual WIFI antenna for a strong wireless
- network signal
- Automatic detection and connection of IP cameras without any manual operation



EASY IP SOLUTION

Distributed by Г

L

HIKVISION

Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T+86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision Poland T +48-22-460-01-50 poland@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision UK T +44-1628-9021-4 support.uk@hikvision.com Hikvision Europe T +31-23-5542770 saleseuro@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Singepore T +65-6684-4718 sg@hikvision.com

Hikvision Middle East T+971-4-8815086 salesme@hikvision.com

Hikvision France T +33(0)1-85-330-444 info.fr@hikvision.com

Hikvision Oceania T +61-2-8599-4233 salesau@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Hong Kong T +852-2151-1761